

U.S. Serial No. 10/710,306
Examiner: Steven J. Ganey
Art Unit No.: 3752
Page 2 of 12

Atty. Docket No.: JD-327A-US

**RECEIVED
CENTRAL FAX CENTER**

AUG 31 2006

IN THE SPECIFICATION

Please amend the specification as follows:

Please amend Paragraph 29 as follows:

Referring to FIGURES 1-4, the support apparatus generally 10 is illustrated in conjunction with a dispensing device 12. The dispensing device was previously referred to above as described in U.S. Patent No. 6,708,901. The support apparatus 10 includes a platform 14 and a back wall 16, as well as cavities 18 providing a first support member which receive the spout 22 of the dispensing device 12. The platform 14 has indented panels 13 which afford an area for placement of product identification labels to indicate the materials being dispensed from the dispenser bottle 55. There are also foot portions 25 and 27 providing a second support member which are pivotally attached to a frame 30 for purposes of supporting containers such as bottle 33 and provide a drip tray when a bottle is not present. These foot portions 25 and 27 have indentations 35 so as to accommodate the bottoms of a bottle such as 33. As seen in FIGURES 1 and 2, there is a hose 40 which is attached to the dispensing tube 15 of dispenser 12 for the purpose of filling bucket 38.

Please amend Paragraph 30 as follows:

Referring to FIGURES 5-7, it is seen that the frame 30 includes a second portion 42 extending essentially at a right angle to [[the]] a vertical first portion 46 of frame 30. This portion 42 supports the foot portions 25 and 27 which they are pivotally attached to frame 30. As best seen in FIGURE 6, frame 30 includes an additional U-shaped portion 44 supporting the platform 14 as by contact with the projections 48. As seen in FIGURE 7, there is connected to the frame 30 a cross-bar member 50 extending behind the wall 16 through which mounting screws 52 can be inserted, such as through the holes 53 as seen in FIGURE 4.

U.S. Serial No. 10/710,306
Examiner: Steven J. Ganey
Art Unit No.: 3752
Page 3 of 12

Atty. Docket No.: JD-327A-US

Please amend Paragraph 31 as follows:

FIGURES 8-10 illustrate a second embodiment generally 10A of the support apparatus. The same reference numerals are employed as previously with respect to similar elements and embodiment 10, except they include the "A" suffix. One of the differences between support apparatus 10 and 10A is [[the]] an additional third support member 60A and the side portions 62A of the frame 30A. It should be noted that the side portions 62A angle inwardly in a direction from the third support member 60A toward the first support member in the form of platform 14A. This provides additional support for dispenser bottle 55A in addition to the support provided by the spout 22A positioned in cavity 18A. Another difference is the funnel 64A. This affords efficient transfer of liquid material from the dispensing device 12A into the hose 40A for bucket filling.